# 2p 4p 8p Pure Nickel Alloy For Lithium 18650 Pure Nichrome Nickel Strip For Battery

#### Basic Information

Place of Origin: China
Brand Name: Victory
Certification: ISO,TUV, RoHS
Model Number: N4,N6,Ni200,Ni201

Minimum Order Quantity: 2kgPrice: \$28-\$32/kg

Packaging Details: Spool package with Carton box, Coil

package with polybag,

• Delivery Time: 5-21 days

• Payment Terms: L/C, T/T, Western Union, MoneyGram

• Supply Ability: 300 tons per month



#### **Product Specification**

Product Name: Pure Nickel Strip
Grade: N4.N6.Ni200.Ni201

Metal: Nickel • Ni(min): 99.95% Resistance (μΩ.m): 1.5 Ultimate Strength (≥ MPa): 462 45 Elongation (≥ %): Surface: Briaht • Density (g/cm3): 8.9 G/cm3 • Resistivity: 1.35±0.07 Melting Point(°C): 1435-1446 °C Application: Chemical Industry

• M.O.Q: 2KG

Highlight:
 8p Pure Nickel Alloy,

18650 Battery Pure Nickel Alloy



## More Images



### **Product Description**

When it comes to Pure Nickel Strip products, we can consider it as a multifunctional metal strip with a wide range of applications and unique characteristics.

The grades of Pure Nickel Strips typically include N4 and N6, both of which are made of high-purity nickel materials to ensure the stability of material quality and performance. The main characteristics of this material are its excellent corrosion resistance, excellent conductivity, and good plasticity.

Pure Nickel Strip exhibits excellent corrosion resistance and can resist the erosion of various chemicals, acids, alkalis, and corrosive gases. This makes it an ideal choice in fields such as chemical engineering, electrochemistry, and battery manufacturing, capable of maintaining stability and reliability in harsh environments.

Specification

Grade	Ni+Co	Cu	Si	Mn	С	Mg	S	Р
N4	99.8	0.015	0.03	0.002	0.01	0.01	0.001	0.00
N6	99.6	0.10	0.10	0.05	0.10	0.10	0.005	0.00
Ni201	≥99.0	≤0.25	≤0.35	≤0.35	≤0.02	1	≤0.01	1
Ni200	≥99.2	≤0.25	≤0.35	≤0.35	≤0.15	1	≤0.01	1
Material			0/32650 nickel str		'	'		

Material	18650/21700/26650/32650 nickel strip			
Material	10030/21700/20030/32030 Hicker Strip			
Dimension	1P to 9P			
Available Space	18.5mm,19mm, 19.5mm, 20.2mm			
Usage	Use for 18650 battery pack			
Package	Nickel strip in roll pack into carton			
Physical properties	High temperature resistant, corrosion resistance,			
Technical support	With imported stamping machine, Japanese Sodick, complete mold (more than 2000 sets of battery industry hardware mold), and can open mold independently.			
Functions	Products are widely used in energy storage battery, new energy vehicles, electric bicycles, solar street lights, power tools and other energy products			
Advantage All materials are degreased and adopt the dry -punching technology to ensure that the product is clean.				

# H shape nickel strip: 1P, 2P 3P, 4P, 5P, 6P, 7P, 8P, 9P

Model Thickness	Distance of two welding centers: 18.5mm (used for battery pack without battery spacer)	Distance of two welding centers: 19mm	Distance of two welding centers: 19.5mm	Distance of two welding centers: 20/20.25mm	
		Width(mm)	Width(mm)	Width(mm)	Width(mm)
1P		8	8	8	8
2P		25.5/27	26.5/27	26.5/27	27
3P		44	46	46	47
4P		62.5	65.5	65.5	67
5P	0.15/0.2mm	81	85	85	87
6P		99.5	104.5	104.5	107
7P		118	124	124	127
8P		136.5	143.5	143.5	147
9P		155	163	163	167

# H shape nickel strip

Model	Thickness	Width	Distance of two welding centers
1P		8	
2P	0.15/0.2mm	23	
3P		39	18.5mm
4P		55	
5P		71	

Туре	Dimension (mm)		Width	Dimension of the Square hole	Nickel Plated steel strip	Pure Nickel		battery ck
				(nn)	Length for per Kg(m)		with holder	without holder
	0.15*7*18.4	18. 4		-	128.3	112.6		√
1P 18650 Nickel strip	0. 15*7*19	19	7	-	127.9	112.1	-√	
IF 10050 NICKEL STEED	0.15*7*19.5	19. 5	,	-			4	
	0.15*7*20.25	20. 25		-	127.6	111.9	-√	
	0. 15*26*19(13. 5*13. 5)	19	26	12*12	47. 2	41. 4	4	
2P 18650 Nickel strip	0. 15*27*19. 5(12*14. 5)	19. 5		12*14.5	48. 9	42. 9	4	
2F 10050 Nickel Strip	0. 15*27*19.75(12.5*12.5)	19.75	27	12. 5*12. 5	47	41. 2	√	
	0. 15*27*20.25(13.5*13.5)	20. 25		13. 5*13. 5	48. 9	42. 9	4	
2P 18650 Nickel strip	0.15*25.5*18.4(11*12.5)	18. 4		11*12.5	48. 9	42. 9		4
Dislocation 2P 18650 Nickel strip	0. 15*25. 5*18. 4 (8*9. 5)	18. 4	25. 5	8*9.5	41. 1	36. 1		4
Dislocation 2P 18650 Nickel strip	0. 15*25. 5*19. 5 (8*9. 5)	19. 5		8*9.5	38. 6	33. 8	4	
	0. 15*44. 5*18. 4 (11*12. 5)	18. 4	44. 5	11*12.5	27. 4	24		4
3P 18650 Nickel strip	0.15*45*19 (12*12)	19	45	12*12	29. 1	25. 5	-√	
or 10000 Nickel Strip	0. 15*47. 5*20. 15 (12.65*12.65)	20. 15	47. 5	12. 65*12. 65	27. 4	24	4	
	0.15*47.5*20.25 (13.5*13.5)	20. 25	41.5	13. 5*13. 5	29. 4	25. 7	4	
	0.15*63*18.5 (11*12.5)	18. 5	63	11*12.5	21. 6	18. 9		4
4P 18650 Nickel strip	0.15*64*19 (12*12)	19	64	12*12	21	18. 4	√	
4r 10000 Nickel Strip	0. 15*67. 95*20. 15 (12. 65*12. 65)	20. 15	67. 95	12. 65*12. 65	19. 6	17. 2	4	
	0.15*67.7*20.25 (13.5*13.5)	20. 25	67	13. 5*13. 5	21. 3	18. 7	-√	
	0.15*83*19 (12*12)	19	83	12*12	16. 4	14. 4	-√	
5P 18650 Nickel strip	0. 15*88. 1*20. 15 (12. 65*12. 65)	20. 15	88. 1	12. 65*12. 65	19. 7	17. 3	-√	
	0.15*87.9*20.25 (13.5*13.5)	20. 25	87. 9	13. 5*13. 5	16. 7	14.6	-√	
6P 18650 Nickel strip	0.15*102*19 (12*12)	19	102	12*12	13. 5	11. 9	-√	
	0.15*108.25*20.15	20. 15	108. 25	12. 65*12. 65	12.6	11	-√	
	0.15*108.1*20.25 (13.5*13.5)	20. 25	108.1	13. 5*13. 5	13. 7	12	4	
•	0.15*121*19 (12*12)	19	121	12*12	11. 5	10	4	
7P 18650 Nickel strip	0. 15*128. 4*20. 15 (12. 65*12. 65)	20. 15	128.4	12. 65*12. 65	10.7	9.4	-√	
	0.15*128.3*20.25 (13.5*13.5)	20. 25	128.3	13. 5*13. 5	11. 6	10. 2	4	
8P 18650 Nickel strip	0.15*140*19 (12*12)	19	140	12*12	10	8.7	4	



Shape	Size(mm)
Wire	0.025-10
Ribbon	(0.05-0.2)*(0.5-6)
Strip	(0.05-0.5)*(5-200)





+8619906119641 victory@dlx-alloy.com victory-alloy.com

NO.32 West Taihu Road, Xinbei District, Changzhou, Jiangsu