

China

Victory

2kg

5-21 days

ISO,TUV, RoHS

N4,N6,Ni200,Ni201

1 - 49 kilograms US\$35.00

package with polybag,

300 tons per month

Spool package with Carton box, Coil

L/C, T/T, Western Union, MoneyGram

Pure Nickel Strip For 18650 21700 26650 32650 32700 Batteries 1P/2P/3P/4P/5P/6P

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:

Our Product Introduction

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

BLX

之信科技有限公司

Product Specification

 Product Name: 	Pure Nickel Strip
Grade:	N4,N6,Ni200,Ni201
• Metal:	Nickel
• Ni(min):	99.5%
 Resistance (μΩ.m): 	1.5
● Ultimate Strength (≥ MPa):	462
 Elongation (≥ %): 	45
• Surface:	Bright
• Density (g/cm3):	8.9 G/cm3
 Resistivity: 	1.35±0.07
 Melting Point(°C): 	1435-1446 °C
 Application: 	Chemical Industry Battery Assembly
• M.O.Q:	2KG
Highlight:	18650 Batteries Pure Nickel Strip, 1P Pure Nickel Strip,



More Images



Product Description

Pure Nickel Strip For 18650 21700 26650 32650 32700 Batteries 1P/2P/3P/4P/5P/6P Introduction:

1. From battery manufacturing to electronics and beyond, our pure nickel strip finds its place in various industries.

2. Its exceptional properties make it a trusted choice for applications that require reliable performance, improved conductivity, and durability.

3. When you choose our pure nickel strip, you can be confident in its high quality and adherence to industry standards.

4. We take pride in delivering a reliable solution that meets the stringent requirements of your projects.

5. Experience the versatility and performance of our pure nickel strip and unlock its potential in powering your applications. Trust in its superior spot welding, low resistance, and the ability to extend battery discharge time – all packaged in a reliable and high-quality product.

Applications:

Our pure nickel strip serves a variety of functions and finds applications in:

1. **Battery manufacturing:** It is used in the production of nickel-cadmium batteries, nickel-hydrogen batteries, and lithium cells.

2. Assembled battery production: It provides secure connections in battery packs.

3. Electric tool industry: It enhances the performance and longevity of electric tools.

4. Special lights industry: It ensures reliable and efficient lighting systems.

5. **Superconductor applications:** Its magnetic properties contribute to generating and maintaining superconductivity.

Specification:

Grade	Ni+Co	Cu	Si	Mn	С	Mg	S	P	Fe
N4	99.8	0.015	0.03	0.002	0.01	0.01	0.001	0.001	0.04
N6	99.6	0.10	0.10	0.05	0.10	0.10	0.005	0.002	0.10
Ni201	≥99.0	≤0.25	≤0.35	≤0.35	≤0.02	/	≤0.01	/	≤0.40
Ni200	≥99.2	≤0.25	≤0.35	≤0.35	≤0.15	/	≤0.01	/	≤0.40

Material	18650/21700/26650/32650 nickel strip
Dimension	1P to 9P
Available Space	18.5mm,19mm, 19.5mm, 20.2mm
	Use for 18650 battery pack
Package	Nickel strip in roll pack into carton
Physical properties	High temperature resistant, corrosion resistance,
1	With imported stamping machine, Japanese Sodick, complete mold (more than 2000 sets of battery industry hardware mold), and can open mold independently.
	Products are widely used in energy storage battery, new energy vehicles, electric bicycles, solar street lights, power tools and other energy products
Advantage	All materials are degreased and adopt the dry -punching technology to ensure that the product is clean.

H shape nickel strip: 1P, 2P 3P, 4P, 5P, 6P, 7P, 8P, 9P

Model	Thickness	Distance of two welding centers: 18.5mm (used for battery pack without battery spacer)	Distance of two welding centers: 19mm	Distance of two welding centers: 19.5mm	Distance of two welding centers: 20/20.25mm
		Width(mm)	Width(mm)	Width(mm)	Width(mm)
1P		8	8	8	8
2P		25.5/27	26.5/27	26.5/27	27
3P		44	46	46	47
4P		62.5	65.5	65.5	67
5P	0.15/0.2mm	81	85	85	87
6P		99.5	104.5	104.5	107
7P		118	124	124	127
8P		136.5	143.5	143.5	147
9P	1	155	163	163	167

H shape nickel strip

Model	Thickness	Width	Distance of two welding centers		
1P		8			
2P	3P 0.15/0.2mm	23			
3P		39	18.5mm		
4P		55			
5P		71			

Туре	Dimension (mm)	Cell spacin g(nn)	Width	Dimension of the Square hole	Nickel Plated steel strip	Pure Nickel	Type of battery pack	
				(nn)	Length for per Kg(m)		with holder	without holder
	0.15*7*18.4	18.4	7	-	128.3	112.6		- 1
1P 18650 Nickel strip	0. 15*7*19	19		-	127.9	112.1	-	
in loose means antip	0.15*7*19.5	19.5		-			1	
	0.15*7*20.25	20. 25		-	127.6	111.9	1	
	0.15*26*19(13.5*13.5)	19	26	12*12	47.2	41.4	4	
2P 18650 Nickel strip	0.15*27*19.5(12*14.5)	19.5		12*14.5	48. 9	42.9	4	
2F 10030 Mickel strip	0. 15*27*19. 75 (12. 5*12. 5)	19.75	27	12.5*12.5	47	41.2	4	
	0. 15*27*20. 25 (13. 5*13. 5)	20. 25		13.5*13.5	48. 9	42.9	4	
2P 18650 Nickel strip	0.15*25.5*18.4(11*12.5)	18.4		11*12.5	48. 9	42. 9		1
Dislocation 2P 18650 Nickel strip	0. 15*25. 5*18. 4 (8*9. 5)	18.4	25. 5	8*9.5	41. 1	36. 1		~
Dislocation 2P 18650 Nickel strip	0. 15*25. 5*19. 5 (8*9. 5)	19.5		8*9.5	38.6	33. 8	4	
	0.15*44.5*18.4 (11*12.5)	18.4	44.5	11*12.5	27.4	24		- 4
3P 18650 Nickel strip	0.15*45*19 (12*12)	19	45	12*12	29.1	25.5	~	
or 10000 Mickel strip	0.15*47.5*20.15 (12.65*12.65)	20.15	47.5	12.65*12.65	27.4	24	4	
	0.15*47.5*20.25 (13.5*13.5)	20. 25	47.0	13.5*13.5	29.4	25.7	4	
	0.15*63*18.5 (11*12.5)	18.5	63	11*12.5	21.6	18.9		- 4
4P 18650 Nickel strip	0.15*64*19 (12*12)	19	64	12*12	21	18.4	4	
A 10000 MICKET Strip	0. 15*67. 95*20. 15 (12. 65*12. 65)	20.15	67.95	12.65*12.65	19.6	17.2	4	
	0.15*67.7*20.25 (13.5*13.5)	20. 25	67	13.5*13.5	21.3	18.7	4	
	0.15*83*19 (12*12)	19	83	12*12	16.4	14.4	-	
5P 18650 Nickel strip	0. 15*88. 1*20. 15 (12. 65*12. 65)	20.15	88.1	12.65*12.65	19.7	17.3	~	
	0.15*87.9*20.25 (13.5*13.5)	20. 25	87.9	13.5*13.5	16.7	14.6	4	
	0.15*102*19 (12*12)	19	102	12*12	13.5	11.9	~	
6P 18650 Nickel strip	0.15*108.25*20.15	20.15	108.25	12.65*12.65	12.6	11	4	
	0.15*108.1*20.25 (13.5*13.5)	20. 25	108.1	13.5*13.5	13.7	12	4	
	0.15*121*19 (12*12)	19	121	12*12	11.5	10	4	
7P 18650 Nickel strip	0.15*128.4*20.15 (12.65*12.65)	20.15	128.4	12.65*12.65	10.7	9.4	~	
	0.15*128.3*20.25 (13.5*13.5)	20. 25	128.3	13. 5*13. 5	11.6	10.2	4	
8P 18650 Nickel strip	0.15*140*19 (12*12)	19	140	12*12	10	8.7	1	



