



Ni200 Ni201 Nickel Strip Customized Lithium Battery Packs Spot Welding

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Victory
- Certification: ISO,TUV, RoHS
- Model Number: N4,N6,Ni200,Ni201
- Minimum Order Quantity: 2kg
- Price: \$28-\$32/kg
- Packaging Details: Spool package with Carton box, Coil package with polybag,
- Delivery Time: 5-21 days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 300 tons per month



Product Specification

- Product Name: Pure Nickel Strip
- Grade: N4,N6,Ni200,Ni201
- Metal: Nickel
- Ni(min): 99.5%
- Resistance ($\mu\Omega\cdot m$): 1.5
- Ultimate Strength (\geq MPa): 462
- Elongation (\geq %): 45
- Surface: Bright
- Density (g/cm³): 8.9 G/cm³
- Resistivity: 1.35 \pm 0.07
- Melting Point($^{\circ}$ C): 1435-1446 $^{\circ}$ C
- Application: Chemical Industry Battery Assembly
- M.O.Q: 2KG
- Highlight: **Ni201 Nickel Strip,**
Lithium Battery Packs Nickel Strip,
Spot Welding Ni200 Nickel Strip



More Images



for more products please visit us on victory-alloy.com

Product Description

Introduction:

Our pure nickel strip stands out with its exceptional properties and performance. Here are some key highlights:

- 1. Superior corrosion resistance:** The pure nickel strip exhibits outstanding resistance to corrosion, ensuring longevity and reliability, even in harsh and corrosive environments.
- 2. Excellent thermal conductivity:** With its high thermal conductivity, our pure nickel strip facilitates efficient heat dissipation and thermal management, making it an ideal choice for applications that require effective temperature control.
- 3. High electrical conductivity:** The pure nickel strip boasts excellent electrical conductivity, allowing for efficient energy transfer and reducing power losses in electrical systems.

Our pure nickel strip – a versatile and high-quality solution designed for a wide range of applications.

Features:

Pure nickel strip is characterized by the following key features:

- 1. Excellent corrosion resistance:** Pure nickel strip exhibits exceptional resistance to corrosion, ensuring its durability and reliability in corrosive environments.
- 2. High electrical conductivity:** The strip possesses excellent electrical conductivity, allowing for efficient flow of electrical current and minimizing power losses in electrical systems.
- 3. Good thermal conductivity:** Pure nickel strip demonstrates good thermal conductivity, facilitating efficient heat dissipation and thermal management in various applications.
- 4. Ductility and malleability:** The strip is highly ductile and malleable, enabling easy shaping and forming to meet specific design requirements.
- 5. Weldability:** Pure nickel strip exhibits excellent weldability, enabling secure and reliable spot welding connections in various assembly processes.
- 6. Customizable dimensions:** The strip is available in a range of customizable dimensions, including width and thickness, to suit specific application needs.

Specification :

Grade	Ni+Co	Cu	Si	Mn	C	Mg	S	P	Fe
N4	99.8	0.015	0.03	0.002	0.01	0.01	0.001	0.001	0.04
N6	99.6	0.10	0.10	0.05	0.10	0.10	0.005	0.002	0.10
Ni201	≥99.0	≤0.25	≤0.35	≤0.35	≤0.02	/	≤0.01	/	≤0.40
Ni200	≥99.2	≤0.25	≤0.35	≤0.35	≤0.15	/	≤0.01	/	≤0.40

Material	18650/21700/26650/32650 nickel strip
Dimension	1P to 9P
Available Space	18.5mm, 19mm, 19.5mm, 20.2mm
Usage	Use for 18650 battery pack
Package	Nickel strip in roll pack into carton
Physical properties	High temperature resistant, corrosion resistance,
Technical support	With imported stamping machine, Japanese Sodick, complete mold (more than 2000 sets of battery industry hardware mold), and can open mold independently.
Functions	Products are widely used in energy storage battery, new energy vehicles, electric bicycles, solar street lights, power tools and other energy products
Advantage	All materials are degreased and adopt the dry -punching technology to ensure that the product is clean.

H shape nickel strip: 1P, 2P 3P, 4P, 5P, 6P, 7P, 8P, 9P

Model	Thickness	Distance of two welding centers: 18.5mm (used for battery pack without battery spacer)	Distance of two welding centers: 19mm	Distance of two welding centers: 19.5mm	Distance of two welding centers: 20/20.25mm
		Width(mm)	Width(mm)	Width(mm)	Width(mm)
1P	0.15/0.2mm	8	8	8	8
2P		25.5/27	26.5/27	26.5/27	27
3P		44	46	46	47
4P		62.5	65.5	65.5	67
5P		81	85	85	87
6P		99.5	104.5	104.5	107
7P		118	124	124	127
8P		136.5	143.5	143.5	147
9P		155	163	163	167

H shape nickel strip

Model	Thickness	Width	Distance of two welding centers
1P	0.15/0.2mm	8	18.5mm
2P		23	
3P		39	
4P		55	
5P		71	

Type	Dimension(mm)	Cell spacing(mm)	Width	Dimension of the Square hole (mm)	Nickel Plated steel strip	Pure Nickel	Type of battery pack	
					Length for per Kg(m)		with holder	without holder
1P 18650 Nickel strip	0.15*7*18.4	18.4	7	-	128.3	112.6	✓	
	0.15*7*19	19		-	127.9	112.1	✓	
	0.15*7*19.5	19.5		-			✓	
	0.15*7*20.25	20.25		-	127.6	111.9	✓	
2P 18650 Nickel strip	0.15*26*19(13.5*13.5)	19	26	12*12	47.2	41.4	✓	
	0.15*27*19.5(12*14.5)	19.5	27	12*14.5	48.9	42.9	✓	
	0.15*27*19.75(12.5*12.5)	19.75		12.5*12.5	47	41.2	✓	
	0.15*27*20.25(13.5*13.5)	20.25		13.5*13.5	48.9	42.9	✓	
2P 18650 Nickel strip	0.15*25.5*18.4(11*12.5)	18.4	25.5	11*12.5	48.9	42.9		✓
Dislocation 2P 18650 Nickel strip	0.15*25.5*18.4(8*9.5)	18.4		8*9.5	41.1	36.1		✓
Dislocation 2P 18650 Nickel strip	0.15*25.5*19.5(8*9.5)	19.5		8*9.5	38.6	33.8	✓	
3P 18650 Nickel strip	0.15*44.5*18.4(11*12.5)	18.4	44.5	11*12.5	27.4	24		✓
	0.15*45*19(12*12)	19	45	12*12	29.1	25.5	✓	
	0.15*47.5*20.15(12.65*12.65)	20.15	47.5	12.65*12.65	27.4	24	✓	
	0.15*47.5*20.25(13.5*13.5)	20.25		13.5*13.5	29.4	25.7	✓	
4P 18650 Nickel strip	0.15*63*18.5(11*12.5)	18.5	63	11*12.5	21.6	18.9		✓
	0.15*64*19(12*12)	19	64	12*12	21	18.4	✓	
	0.15*67.95*20.15(12.65*12.65)	20.15	67.95	12.65*12.65	19.6	17.2	✓	
	0.15*67.7*20.25(13.5*13.5)	20.25	67	13.5*13.5	21.3	18.7	✓	
5P 18650 Nickel strip	0.15*83*19(12*12)	19	83	12*12	16.4	14.4	✓	
	0.15*88.1*20.15(12.65*12.65)	20.15	88.1	12.65*12.65	19.7	17.3	✓	
	0.15*87.9*20.25(13.5*13.5)	20.25	87.9	13.5*13.5	16.7	14.6	✓	
	0.15*102*19(12*12)	19	102	12*12	13.5	11.9	✓	
6P 18650 Nickel strip	0.15*108.25*20.15	20.15	108.25	12.65*12.65	12.6	11	✓	
	0.15*108.1*20.25(13.5*13.5)	20.25	108.1	13.5*13.5	13.7	12	✓	
	0.15*121*19(12*12)	19	121	12*12	11.5	10	✓	
	0.15*128.4*20.15(12.65*12.65)	20.15	128.4	12.65*12.65	10.7	9.4	✓	
7P 18650 Nickel strip	0.15*128.3*20.25(13.5*13.5)	20.25	128.3	13.5*13.5	11.6	10.2	✓	
	0.15*140*19(12*12)	19	140	12*12	10	8.7	✓	



Changzhou Victory Technology Co., Ltd



+8619906119641



victory@dlx-alloy.com



victory-alloy.com

NO.32 West Taihu Road, Xinbei District, Changzhou, Jiangsu