for more products please visit us on victory-alloy.com

Bright Incoloy 800 Strip High Tensile Nickel Alloy Strip

Basic Information

• Place of Origin: China • Brand Name: Victory

• Certification: CE,ROHS,ISO 9001 Model Number: Incoloy 800 • Minimum Order Quantity: 1 Kg

• Price: 30 - 499 kilograms \$46.90

 Packaging Details: Packed as coil. Special packaging

requirements can also be accommodated.

OEM is also acceptable

7 to 20 Days . Delivery Time:

L/C, D/A, D/P, T/T, Western Union, • Payment Terms:

MoneyGram

• Supply Ability: 100 Ton/Tons per Month



Product Specification

• Product Name: Incoloy 800 Strip Material: Ni Cr Fe • Ni (Min): 30% Resistance (μΩ.m): 1.15 • Powder Or Not: Not Powder

• Ultimate Strength (≥ MPa): 790 Elongation (≥ %): 30 Density (g/m3): 8.4 G/cm3

Application: Industrial, Construction, Building

• Surface: Bright • Size: Customized

Processing Service: Decoiling, Cutting, Bending • Highlight: Bright Incoloy 800 Strip,

Incoloy 800 Nickel Alloy Strip Incoloy 800 Alloy Strip



Product Description

Introduction:

- 1. Incoloy 800 strip is available in various thicknesses and widths to suit specific requirements.
- 2. The strip's composition typically consists of approximately 30% nickel, 46% iron, and small amounts of chromium, aluminum, and titanium.
- 3. Incoloy 800 strip is a high-performance material known for its excellent high-temperature strength, corrosion resistance, thermal stability, and creep resistance.
- 4. It belongs to the Incoloy family of superalloys and is commonly used in industries that require reliable performance at elevated temperatures.

1. Chemical processing: It is used in components such as heat exchangers, furnace parts, and piping systems.

- 2. Power generation: Incoloy 800 strip is employed in gas turbine components, steam generators, and heat recovery systems.
- 3. Aerospace and aviation: It finds applications in aircraft engine components, such as combustion chambers and afterburners.
- 4. Heat treatment industry: Incoloy 800 strip is suitable for fixtures, baskets, and radiant tubes used in heat treatment furnaces that operate at high temperatures.

Size dimension range:

Wire: 0.01-10mm

Strip: 0.05*5.0-5.0*250mm

Bar: φ4-50mm;Length 2000-5000mm

Pipe: φ6-273mm;δ1-30mm;Length 1000-8000mm

Sheet: δ 0.8-36mm; Width 650-2000mm; Length 800-4500mm

Incoloy series:800,800H,800HT,825

Parameter:

Item	800	800H	800HT	825	925
С	≤0.1	0.05-0.1	0.06-0.1	≤0.05	≤0.03
Mn	≤1.5	≤1.5	≤1.5	≤1	≤1
Fe	rest	rest	rest	rest	rest
Р				≤0.02	≤0.03
S	≤0.015	≤0.015	≤0.015	≤0.03	≤0.03
Si	≤1	≤1	≤1	≤0.5	≤0.5
Cu	≤0.75	≤0.75	≤0.75	1.5-3	1.5-3
Ni	30-35	30-35	30-35	38-46	42-46
Al	0.15-0.6	0.15-0.6	0.15-0.6	0.2-1	0.15-0.5
Ti	0.15-0.6	0.15-0.6	0.15-0.6	0.6-1.2	1.9-2.4
Cr	19-23	19-23	19-23	19.5-23.5	19.5-23.5
Мо	- -	- -		2.5-3.5	2.5-3.5





Changzhou Victory Technology Co., Ltd



+8619906119641



victory@dlx-alloy.com victory-alloy.com

