# High Temperature Nimonic Incoloy 800H Strip For Industrial Construction

#### Basic Information

Place of Origin: China Brand Name: Victory

Certification: CE,ROHS,ISO 9001
Model Number: Incoloy 800H
Minimum Order Quantity: 1 Kg

• Price: 30 - 499 kilograms \$46.90

• Packaging Details: Packed as coil. Special packaging

requirements can also be accommodated.


OEM is also acceptable

• Delivery Time: 7 to 20 Days

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

• Supply Ability: 100 Ton/Tons per Month



#### **Product Specification**

Product Name: Incoloy 800H Strip

Material: Ni Cr Fe
Ni (Min): 32%
Resistance (μΩ.m): 1.15
Powder Or Not: Not Powder
Ultimate Strength (≥ MPa): 790
Elongation (≥ %): 30
Density (g/m3): 8.4 G/cm3

Application: Industrial, Construction, Building

Surface: BrightSize: Customized

• Processing Service: Decoiling, Cutting, Bending

• Highlight: Incoloy 800H Strip, Nimonic Incoloy 800H Strip,

32% Ni Incoloy Alloy Strip



## Product Description

#### Introduction:

- 1. Incoloy 800H strip is a specialized material renowned for its outstanding performance in high-temperature environments.
- 2. Made from the Incoloy 800H alloy, Incoloy 800H strip is a thin, flat metal sheet available in various thicknesses and widths.
- 3. With a composition consisting of approximately 32% nickel, 46% iron, and small amounts of chromium, aluminum, and titanium, it offers a unique combination of properties.
- 4. It is widely employed in industries requiring reliable performance in extreme environments

#### Features:

1. Superior high-temperature corrosion resistance: Incoloy 800H strip demonstrates exceptional resistance to oxidation, carburization, and nitridation.

- 2. Enhanced mechanical properties: Compared to Incoloy 800, Incoloy 800H strip boasts improved tensile strength, creep resistance, and rupture strength at elevated temperatures.
- 3. Outstanding creep resistance: The strip's remarkable resistance to creep deformation, even under prolonged high-temperature stress.

### Size dimension range:

Wire: 0.01-10mm

Strip: 0.05\*5.0-5.0\*250mm

Bar: φ4-50mm;Length 2000-5000mm

Pipe: φ6-273mm;δ1-30mm;Length 1000-8000mm

Sheet: δ 0.8-36mm; Width 650-2000mm; Length 800-4500mm

Incoloy series:800,800H,800HT,825

#### **Parameter:**

Item	800	800H	800HT	825	925
С	≤0.1	0.05-0.1	0.06-0.1	≤0.05	≤0.03
Mn	≤1.5	≤1.5	≤1.5	≤1	≤1
Fe	rest	rest	rest	rest	rest
P		<b>-</b> -		≤0.02	≤0.03
S	≤0.015	≤0.015	≤0.015	≤0.03	≤0.03
Si	≤1	≤1	≤1	≤0.5	≤0.5
Cu	≤0.75	≤0.75	≤0.75	1.5-3	1.5-3
Ni	30-35	30-35	30-35	38-46	42-46
Al	0.15-0.6	0.15-0.6	0.15-0.6	0.2-1	0.15-0.5
Ti	0.15-0.6	0.15-0.6	0.15-0.6	0.6-1.2	1.9-2.4
Cr	19-23	19-23	19-23	19.5-23.5	19.5-23.5
Мо				2.5-3.5	2.5-3.5





Changzhou Victory Technology Co., Ltd



+8619906119641



victory@dlx-alloy.com victory-alloy.com

