

China

Victory

FeCrAl

ISO SGS

1400-1520°C Melting Point Ferro Silicon Alloy For Industrial Applications

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:



Ш

BLX

戰之信科技有限公司

Product Specification

Highlight:

1400-1520°C Ferro Silicon Alloy, Industrial Applications Ferro Silicon Alloy, Ferro Silicon Alloy Tube



More Images



Product Description:

The FeCrAl Alloy is available in wire form, with a density of 7.1. Its elongation ranges from 20-30%, making it a flexible and durable material. It can be customized to any length depending on the customer's specific needs. The FeCrAl Alloy is packaged in a wooden box, ensuring safe transit and storage. Its packaging is designed to protect the wire from any damage during transportation. This ensures that the wire arrives at its destination in perfect condition. The FeCrAl Alloy is a ferro silicon alloy, which means it is made by combining iron with silicon and other elements to create a highly durable and stable material. It is also commonly used in the production of ferro alloy slag, which is used in the production of steel and other metals. This makes it an essential material in the manufacturing industry.

Features:

Product Name: FeCrAl Alloy

Tensile Strength: 600-800 MPa

Corrosion Resistance: Excellent

Package: Wooden Box

Port: Shangahi, China

Nickel: 80%

Our FeCrAl Alloy product is a high-strength alloy with tensile strength of 600-800 MPa. It is known for its excellent corrosion resistance, making it a durable and reliable choice for various applications. The product is packaged in a sturdy wooden box for safe transportation. We ship from the port of Shanghai, China. This alloy contains 80% nickel, making it a popular choice in the production of Ferro Alloy Slag and Alloy Tool Steel.

Product Attribute	Value	
Ferro Alloy Metal	FeCrAl Alloy	
Iron-Base Alloy	Yes	
Corrosion Resistance	Excellent	
Resisivity	1.45	
Grade	Cr22Al4.5, 0Cr25Al5	
Length	Depend On Customer	
Nickel	80%	
Port	Shanghai, China	
Density	7.1	
Shape	Wire	
Elongation	20-30%	
Package	Wooden Box	

Technical Parameters:

Applications:

1. Heating Elements: Victory FeCrAl Alloy is widely used in heating elements due to its high resistance to heat and corrosion. This alloy is perfect for use in high-temperature environments, and it can withstand temperatures of up to 1400°C. It is commonly used in industrial furnaces, heaters, and ovens.

2. Ferro Alloy Slag: This alloy is also used in the production of ferro alloy slag. The alloy is melted down and used to create the slag, which is then used to produce other alloys such as alloy tool steel. The Victory FeCrAl Alloy is an essential component in the manufacturing of these alloys.

3. Alloy Tool Steel: The Victory FeCrAl Alloy is also used in the production of alloy tool steel. This steel is used in the manufacturing of tools and machine parts. The alloy's high resistance to heat and corrosion makes it an ideal choice for use in high-stress environments.

The Victory FeCrAI Alloy is manufactured in China JiangSu and has a minimum order quantity of 5. The alloy's tensile strength ranges from 600-800 MPa, and it is supplied as a rod. The alloy comes in a bright status and is packaged in a wooden box for safe transportation. The Victory FeCrAI Alloy has excellent corrosion resistance, making it a popular choice for many industries.

Customization:

Our customization services for FeCrAl Alloy include altering the length, shape, and size of the product. We also offer customization for other Ferro Silicon Alloy and Alloy Tool Steel products. Contact us to learn more about our product customization services.

Support and Services:

Our FeCrAl alloy product technical support team is available to assist with any questions or concerns related to the product's performance, properties, or applications. We also offer a range of services to support our customers' needs, including:

Custom alloy design and development

Material selection and testing

Technical consultation and troubleshooting

Training and education on FeCrAl alloy properties and applications

Product testing and analysis

Quality assurance and control

Our goal is to provide exceptional customer service and ensure that our FeCrAI alloy products meet or exceed your expectations. Please don't hesitate to contact us for technical support or to discuss our services in more detail.

Packing and Shipping:

Product Packaging:

The FeCrAl Alloy product will be packaged in durable and secure boxes to ensure safe transportation. Each box will contain the product in sealed bags to prevent any damage from moisture or dust. Shipping:

Shipping will be through a reliable courier service. The product will be shipped with care to ensure it reaches the destination in good condition. Customers can track their shipment through a tracking number provided to them.

FAQ:

- Q: What is the brand name of this product?
- A: The brand name of this product is Victory.
- Q: What is the model number of this product?
- A: The model number of this product is FeCrAl Alloy.
- Q: Where is this product made?
- A: This product is made in China JiangSu.
- Q: What is the minimum order quantity for this product?
- A: The minimum order quantity for this product is 5.
- Q: Is this product covered by warranty?
- A: We do not provide warranty-related information for this product. Please contact us for further assistance.

	VK °	Changzhou Victory Techn	ology Co., Ltd	
٩	+8619906119641	victory@dlx-alloy.com	© victory-alloy.com	
NO.32 West Taihu Road, Xinbei District, Changzhou, Jiangsu				